

CO₂ Back-up System

BS-1 is to ensure optimal security for critical samples stored in Ultra-Low Temperature Freezers. It controls injection of CO₂ into freezer when freezer temperature rises above the preset temperature value. It also reminds users to fill or replace their CO₂ cylinders when pressure is low.



Advantage

- Compact design, small footprint, can be placed on freezer top
- Temperature display, setting temperature adjustable by user
- Unique low CO₂ alarm, reminding user to change CO₂ cylinder in time
- USA-made ASCO brand ultra-low temperature electromagnetic valve

Safety

- Valve test button to check whether electromagnetic valve works normally
- High/Low temperature alarm, low battery alarm, low CO₂ alarm
- Stop injection of CO₂ when door opens, protecting user from being injured by liquid CO₂ (need to be connected with ULT freezer door switch).

Reliability

- Stainless steel construction, rust-free, easy cleaning
- Hose & injection tube with sponge cover for insulation
- Rechargeable battery for 48 hours working time



	Model	BS-1
Basic	Climate Class	N/ST/T
	Cooling Type	Direct Cooling
	Refrigerant	Liquid CO ₂
Performance	Cooling Performance (°C)	-70
	Temperature Range (°C)	-40~-70
Control	Controller	Thermostat
	Display	LED
	Temperature Increment (°C)	1
Electrical	Power Supply	AC 100~240V, 50/60Hz
	Power (W)	20
	Electrical Current (A)	0.25
Weight & Dimension	Net/Gross Weight	11.2/13.6kg
		24.7/30lbs
	Exterior Dimension (W*D*H)	200*400*160 (mm)
		7.8*15.7*6.3 (in)
Functions	Packing Dimension (W*D*H)	370*530*330 (mm)
		14.6*20.9*13 (in)
	High/Low Temperature Alarm	Yes
	Low Liquid CO ₂ Alarm	Yes
Accessories	Low Battery Alarm	Yes
	Sensor Failure Alarm	Yes
	Main Power Failure Alarm	Yes
	Valve Open Indicator Light	Yes
Accessories	Main Power On Indicator Light	Yes
	Valve Test Button	Yes
	Hose (connecting backup system & CO ₂ cylinder)	3 meter
Accessories	Injection Tube (connecting backup system & freezer)	2 meter

