W Series

Cryogenic Freezer, Wide Open

W series liquid nitrogen storage system provides ideal storage conditions for biological samples. Supported by LN_2 automatic filling system and temperature & LN2 level monitoring system, W series cryogenic freezers provide all-round protection to precious sample, assisting life science research and cell therapy applications.

Based on the actual needs of users, Antech has innovatively optimized the performance, structure and control system of cryogenic freezer to meet the user's highest standard of large-capacity storage requirements.



Features

- Multiple capacity freezers, from 175L to 600L, 2.0ml vials storage capacity from 10,000 to 40,500.
- Excellent temperature uniformity and stability, enabling samples to be stored at controlled cryogenic environment.
- Excellent vacuum performance and structural design ensure minimum liquid nitrogen consumption and lower storage costs.
- Advanced temperature, liquid level monitoring and alarm system, and can realize remote monitoring.
- Automatic supply of liquid nitrogen, safe and labor-saving.
- The liquid nitrogen supply system is controlled by multiple solenoid valves, which can effectively prevent the overflow of liquid nitrogen and sample contamination caused by high LN₂ level.
- Manual filling available under special circumstances.
- Compatible with vapor phase and liquid phase storage modes, users can choose according to their needs.
- The optimized mechanism design realizes high-density storage to save space.

Humanized Design

- Defog function, easier to find samples and shorten lid opening time.
- The remote alarm interface can be connected to the central alarm system.
- Optional backup battery in case of power failure.
- Optional vacuum jacketed hose for lower liquid nitrogen consumption.
- Optional vapor platform, for vapor phase storage of bio-specimen.



Vacuum jacketed hose

Advanced Control System

- HMI human-machine interactive touch screen, display temperature, liquid level, temperature curve and alarm information.
- Important events such as temperature, alarm, liquid nitrogen fill, can be checked, and can also download through USB disk.
- Various alarms, and the alarm information can be stored and downloaded through the USB disk.
- Operating data, such as temperature and liquid level, can be stored for up to 10 years.
- Optimized structure design to achieve the best sample storage density and save space.



Why W Series

- High density storage
 - Compared with similar products, W series freezers have a small footprint and can store a large number of samples. It truly realizes high-density storage, which not only saves space, but also reduces the storage cost per sample. Both horizontal and vertical rack systems available.
- Advanced temperature monitoring system
 The monitoring system based on microprocessor and platinum temperature probe can display the maximum and minimum temperature inside the tank in real time with an accuracy of ±1°C. The user can set the alarm point by himself, with the option of alarm mute.
- Automatic LN₂ filling & level monitoring system
 The liquid level monitoring system based on high-precision differential pressure sensor displays the liquid level in real time to ensure the safety and reliability of the automatic filling of liquid nitrogen. The color touch screen can display: top temperature, bottom temperature, liquid level height, daily liquid nitrogen consumption and other parameters.
- Warm gas bypass
 - The warm gas bypass design can remove the high temperature nitrogen (gas) in the pipeline before the liquid nitrogen is injected, so as to ensure that only ultra-low temperature liquid nitrogen is injected into freezer, which avoids the temperature fluctuation in the freezer & thermo shock to samples during filling process, protecting the safety of samples.

Racks







Square rack/ Horizontal rack

Slim rack/ Vertical rack	Description	Vial	Dimension, W×D×H(mm)		
CFH-5-2	5 layer, for 100/81-well boxes	1.2/2ml	138*58*710		
Square rack/ Horizontal rack Description		Vial	Dimension, W×D×H(mm)		
CFC-13-2	13 layer, for 100/81-well boxes	1.2/2ml	139*139*751		
CFC-13-2S	13 layer, for 25-well boxes	1.2/2ml	81*81*751		

Specification

Model Mariana de la compania del compania del compania de la compania del compania del compania de la compania del compania dela compania del compania del compania del compania del compania de		W100		W240		W380	
	Maximum storage capacity	Liquid	Vapor	Liquid	Vapor	Liquid	Vapor
	PETG 1/4cc straw	180400	144320	397700	318160	639600	511680
-	PETG 1/2cc straw	80300	64240	177025	141620	284700	227760
traw F	HSV CBS high security straws	80300	64240	177025	141620	284700	227760
	High security CBS straws	49500	39600	109125	87300	175500	140400
	Number of canisters (φ70mm)	44	44	97	97	156	156
	Goblet (φ65mm) per canister	5	4	5	4	5	4
	1.2 &2ml vial	10725	9900	26325	24300	41275	38100
mlvial F	Number of large rack (81/100-place box)	7	7	19	19	30	30
-	Number of small rack (25-place box)	5	5	5	5	7	7
	2" Boxes per rack	13	12	13	12	13	12
-	5ml vial (81-place)	3969	3402	10773	9234	17010	14580
iml vial	Number of racks	7	7	19	19	30	30
	3.75" Boxes per rack	7	6	7	6	7	6
hml F	Numbers of blood bag	763	763	1694	1694	2681	2681
lood bag	Number of frames	109	109	242	242	383	383
	Bags per frame	7	7	7	7	7	7
OI	Numbers of blood bag	476	476	1085	1085	1715	1715
lood bag	Number of frames	68	68	155	155	245	245
	Bags per frame	7	7	7	7	7	7
250ml	Numbers of blood bag	270	216	595	476	970	776
lood bag	Number of frames	54	54	119	119	194	194
	Bags per frame	5	4	5	4	5	4
	Numbers of blood bag	210	168	475	380	760	608
00ml lood bag	Number of frames	42	42	95	95	152	152
	Bags per frame	5	4	5	4	5	4
0001	Numbers of blood bag	144	144	332	332	528	528
100ml blood bag	Number of frames	36	36	83	83	132	132
	Bags per frame	4	4	4	4	4	4
	Numbers of blood bag	84	84	196	196	312	312
700ml blood bag	Number of frames	21	21	49	49	78	78
	Bags per frame	4	4	4	4	4	4
			LN2 Capa	city			
LN2 capac	sity (L)	194	13	413	28	643	43
nnor diamot	tor (mm)		Dimension		200	100	<u> </u>
Inner diameter (mm)		550		800		1000	
Usable height (mm)		785		785		785	
Overall height (mm)		1300		1300 270		1300 395	
Weight empty (kg) Weight full, liquid phase (kg)		160		606		918	
vveignt iuli, i	ilquid pi iase (kg)	ë	Functions		006	918	3
Controller		Touch screen		Touch screen		Touch screen	
Full auto fill		Standard		Standard		Standard	
Data storage/ USB port/ RS485 port		Standard		Standard		Standard	
Data storage/ USB port/ RS485 port Defog		Standard		Standard		Standard	
Step Step		Standard		Standard		Standard	
			Accessor			Otari	
Backup battery		Optional		Optional		Optional	
Vacuum jacketed hose		Optional		Optional		Optional	
Vapor platform		Optional		Optional		Optional	
Inventory rack		Optional		Optional		Optional	
Wi-Fi connection & cloud access		Optional		Optional		Optional	

^{* 25}ml blood bag: Pall MEDSEPTM 25 mL, OriGen CS 25; 50ml blood bag: Fenwal 4R9951, OriGen CS 50;

250ml blood bag: Fenwal 4R9953 & 4R5461, OriGen CS 25 or CryoMACS 50 & 250; **500ml blood bag:** Fenwal 4R9955 & 4R5462, OriGen CS 500; **200ml blood bag:** Gambro DF-200 or CryoMACS 50 & 250; **700ml blood bag:** Gambro DF-700, OriGen CS 1000 or CryoMACS 500& 750 & 1000.