

# CryoFiller Series

## Automatic LN<sub>2</sub> Doser

CryoFiller automatic liquid nitrogen filling system is designed to inject LN<sub>2</sub> into containers at required pace. After filling into container, liquid nitrogen vaporizes to nitrogen gas and expel air out of container. As a result, oxygen and humidity concentration are reduced, and a suitable pressure is built in container.



### Features

- Siemens touch screen controller and PLC platform, fully automatic operation.
- Adjustable filling pace, up to 1200 CPM in discrete dosing mode or 2000 CPM in continuous injection mode.
- Speed sensor: real-time detection of bottle movement speed, filling speed will be adjusted accordingly.
- Product sensor: installed at upstream of the filling machine, detecting whether bottle is coming. If no bottle coming, liquid nitrogen will not be injected to avoid waste.
- ±3% accuracy of dose weight.
- Electric heating at nozzle, prevent condensation water and freezing ice.
- 3 sizes nozzles are supplied as standard, customized nozzle available.
- Gas-liquid separator to guarantee liquid nitrogen is injected.
- Vacuum insulation for low liquid nitrogen consumption.
- Imported high quality electromagnetic valve for high reliability.
- Stainless steel SUS304 material for easy cleaning and no rust.



## Benefits

- Inert packaging (low oxygen concentration) maintains product freshness and extends product shelf life.
- Reduce the gram weight of PET, lower cost and more environmentally friendly.
- Maintain the original shape of lightweight bottle, keep the hardness of the bottle wall consistent, and improve labeling efficiency.
- Build a suitable bottle pressure and eliminate the problem of flat bottles.
- Enhance product stacking capacity and improve warehouse space utilization.
- Maintain the high quality of organic products.

## Containers applicable

- Plastic bottle: soft drink, edible oil, mineral water
- Aluminum can: soft drink
- Steel can: milk powder, protein powder, organic supplement powder
- Glass bottle: wine



## Specification

Model	CryoFiller-L	CryoFiller-S
Maximum Discrete Dosing Speed (CPM)	800	200
Continuous Stream Dosing Speed (CPM)	2000	2000
Dose Duration	15 ~ 1000 ms	15 ~ 1000 ms
Nozzle Size	1.0mm, 1.2mm, 1.5mm, 1.8mm, 2.5mm	1.5mm, 2.0mm, 2.5mm, 3.0mm
Accuracy by Dose Weight	±5%	±5%
LN <sub>2</sub> per Dose	0.01-14 g	0.01-14 g
Touch Screen Display	Siemens	Siemens
PLC Platform	Siemens	Siemens
Speed Sync Compensation	√	√
Injection Positioning Tech	√	√
Fixed Delayed Injection	√	√
Constant Speed Mode	√	√
Vacuum Insulation	√	√
LN <sub>2</sub> Consumption	0.20 L/h	0.15 L/h
Material	SUS304	SUS304
Weight	15Kg	12Kg
Power	100W	100W
Power Supply	110~240V,50/60Hz	110~240V,50/60Hz
LN <sub>2</sub> Supply Pressure	≤0.15Mpa	≤0.15Mpa
Pressurized Air Pressure (N <sub>2</sub> recommended)	0.5~0.65Mpa	0.5~0.65Mpa