LyoAir series Laboratory freeze dryer

Optimize and simplify your freeze-drying process

Taking advantage of the experience and knowledge in freeze drying, Antech offers LyoAir series ready-to-use freeze-drying system, fully equipped with universal drying package & vacuum pump.

LyoAir series freeze dyers are compact in design, high-efficiency in performance, smart in operation, and dependable in daily use.



Innovative features

- Compact, high-performance laboratory systems with a small footprint
- 7" touch screen installed with LyoBasic operating system
- Built-in ice condenser coils for higher efficiency
- Low noise level: 48 dB(A)
- High quality vacuum pump

LyoBasic touch screen control system

7" touch screen controller, installed with LyoBasic operating system, assisting users to similify the freeze-drying process.

- Display of ice condenser temperature and vacuum degree
- Product temperature display according to sublimation pressure curve
- Historical data recorder for convenient analysis of processing
- Password access protection





Advanced cooling system

- -55°C: single compressor system, high efficiency
- -85°C: 2-compressor cascade system, cold trap temperature reaches -85°C within 10 minutes
- SECOP brand compressor for durable use

Optimized flange seal

- Flat surface & L-shaped sealing ring design, no need for extra manual pressure
- Vacuum grease not required, easier to use and clean
- Proven excellent sealing performance for long-term use



Choose the system fits your application best!



Ice capacity

Max. ice capacity	Performance	Models	
4 kg	4 kg/24h	LyoAir 4S, LyoAir 4M	

Temperature level

Temperature level	Temperature	Cooling system	Typical application area		
S	-55°C	1 compressor	Aqueous products		
Μ	-85°C	2 compressors cascade	Products with low freezing points		

*For vacuum controlled freeze drying process, please choose LyoPro series.

*For organic solvent application, please choose LyOrganic series freeze dryers.

The UNIVERSAL package with special price

Start your lyophilization with our universal package, which offers both manifolds and shelves, fulfilling most applications for successful processes every day.

The LyoAir Series with UNIVERSAL package contains:

- LyoAir freeze dryer main machine
- Vacuum gauge
- Acrylic chamber with 8 connections (flask optional)
- 4-layer shelves with unique ShelFlex™ design
- Vacuum pump & vacuum hose



ShelFlex™ design

Unique ShelFlex™ design, various configurations with different number of shelves and spacing are available.

Shelves					
Configuration	Number	Φ	Area	Spacing	
1	2	265 mm	0.10 m ²	140 mm	
2	3	265 mm	0.15 m²	105 mm	
3	4	265 mm	0.20 m ²	70 mm	
4	8	265 mm	0.40 m ²	35 mm	

*For configuration 4, another 4 pcs of shelves to be ordered as optional.

Advantages

- All-inclusive package, avoid confusion in accessory selection
- ShelFlex™ design, adjustable shelf number and spacing with flexibility
- Cost-effective, fulfill more applications with lower cost
- Fast delivery, UNIVERSAL package always in stock for urgent demand

Various freeze-drying packages for different applications











Manifold		Shelves				
No.	Number of connection valves	Number	Φ	Area	Spacing	Stopper
1	8	4	265 mm	0.20 m ²	70 mm	-
2	8	2	265 mm	0.10 m ²	140 mm	•
8	-	4	265 mm	0.20 m ²	70 mm	-
4	-	2	265 mm	0.10 m ²	140 mm	•
6	8	-	-	-	-	-

*Package 1, also named as "universal package", is recommended and supplied as standard configuration.

Specification





	Model	LyoAir 4S	LyoAir 4M
Basic	Туре	Desktop	Desktop
lce condenser	Temperature	-55°C	-85°C
	Max. ice capacity	4 kg	4 kg
	Chamber volume	6.5 L	6.5 L
	Performance	4 kg/24h	4 kg/24h
	Display	7" touch screen	7" touch screen
	Operating system	LyoBasic	LyoBasic
	Ice condenser temperature display	•	•
	Product temperature sublimation	•	•
	Vacuum degree display	•	•
Control	Vacuum gauge type	Thermocouple	Thermocouple
	Vacuum control	-	-
	Vacuum venting	Manual	Manual
	Hot gas defrosting	-	-
Cooling	Number of compressor	1	2
system	Compressor brand	SECOP	SECOP
	Voltage (V/Hz)	220/50;220/60;120/60	220/50;220/60;120/60
Power	Rated power	900 W	1400 W
Noise level	Freeze dryer	48 (dB)	48 (dB)
Dimensions	Main unit (W x D x H)	400*430*550 mm	400*430*550 mm
Weight	Main unit	47 kg	60 kg
Universal drying package	Drying chamber	Acrylic	Acrylic
	Shelves	4	4
	Number of rubber connection valves	8	8
	Flask	0	0
	Vacuum pump	•	•
Vacuum - pump _	Oil mist filter	•	•
	Vacuum pump hose	•	•
	1	1	1

The data provided refers to the base unit with ambient conditions of +10 °C to +25 °C. Subject to change without prior notice.

Basic equipment
O Optional