-86°C Portable ULT Freezer 25 liter


Antech CryoExpress series ultra low temperature portable freezer is compact in size, light in weight, and powerful in cooling. Taking advantages of advanced Stirling cooling technology, CryoExpress series offer wide range accurate temperature control from ambient temperature to -86 C ultra low temperature, which can be used for transportation of biological sample, cells, vaccine, pharmacy, etc.

The portable freezer can be powered with 12²24v DC on a moving vehicle or vessel, or by a power bank. By using adapter, CryoExpress series freezer can be powered and charged with 100²240V AC power supply.



Features

- Precise temperature control Fast cooling speed and uniform internal temperature
- High energy efficiency Designed for space and energy efficiency, the ultra-low temperature freezer uses less than 2.8 kWh/day at -80°C
- Compatible with multiple power sources The portable ULT freezer plugs into any 110V–240V outlet, worldwide, and can even run on 12V DC power with an automotive adapter
- Compact and lightweight design Weighing only 17.5kg, the portable ULT freezer can easily and inexpensively be shipped anywhere in the world
- User-friendly operation and maintenance The operation touch panel is easy to operate and set up



Utilizes 100% natural refrigerant, supporting -sustainable and eco-friendly operation
Use natural refrigerants, which are more environmentally sustainable and eliminate the need for special export shipping classifications

WHY CHOOSE STIRLING COOLING TECHNOLOGY?

The revolutionary ultra-low temperature freezer was equipped with Stirling compressor. The Stirling refrigeration compressor is a mechanical chiller driven by electricity.

With its compact and field-proven, free-piston Stirling engine technology, it brings portable, precisely controlled ULT freezer storage anywhere there is a need for patient care, testing or specimen collection.

Advantages:

• Simplified structure

- Operates without tilt angle restrictions
- High efficiency with low energy consumption
- Rapid freezing capability
- Long lifespan and maintenance-free

-86°C Portable ULT Freezer

	Model	MMF-2
Performance	Temperature range	-86 °C to 18 °C
	Climate type	SN/N
	Cooling motor	Free-piston Stirling engine
	Controller	Microprocessor controller
	Door lock	Yes
	Defrost	Manual
	Over temperature alarm	Yes
	Liner material	SUS304
Capacity & size	Capacity	25L
	Number of 81/100-place 2" boxes	18
	Internal dimensions, W x D x H	250*300*300mm
	External dimensions, W x D x H	392*455*616mm
	Net weight	17.5kg
Power	Power supply	100V~240V AC, 50/60 Hz; 12~24V DC
	Rated power	100W
	Power cord	AC adapter & power cord, DC power cord
Shipping	Packing W x D x H	480*530*710mm
	Gross weight	21kg