

-150°C Cryogenic Freezer

The -150 °C cryo freezer provides a safe, convenient and economical alternative for long term storage for a variety of biological specimens at cryogenic temperature (below -135°C).

Compared with liquid nitrogen containers, there is no need to supply liquid nitrogen for mechanical freezers. It is easier to use and contamination risk caused by liquid nitrogen is avoided.

ANTECH adopted innovative 2-compressor cascade cooling system for its cryogenic freezers, realizing lower power consumption, faster cooling rate and lower noise level.



LOW CO2
EMISSIONS



NATURAL
REFRIGERANT



CFC /HCFC
FREE



HIGH/LOW
TEMPERATURE ALARM



POWER FAILURE
ALARM



DIRECT
COOLING



SAFETY DOOR
LOCK

PERFORMANCE

- Optimized cooling system & high efficiency hydrocarbon refrigerant.
- SECOP brand compressor & EBM brand blower.
- High density polyurethane forming for insulation.

ALARMS

- High temperature
- Low temperature
- Power failure
- Sensor error

ERGONOMIC DESIGN

- Forming inner doors for better insulation and less frost
- Stainless steel interior for easy cleaning
- Ultra-quiet design reduces noise level
- Optional slim rack for convenient operation

SAFETY

- Safety door lock, preventing unauthorized access
- Access port for additional temperature probe
- Optional online monitoring system
- Optional CO2/LN2 backup system

ENVIRONMENT FRIENDLY

- Natural refrigerant compliant with EPA and SNAP non-ozone depleting mandates
- CFC-Free polyurethane foaming insulation
- High efficiency cooling system for lower energy consumption and less carbon emission

-150°C

Cryo Freezer



Model		MDF-150C118			MDF-150C208
Main specifications	Type	Chest			Chest
	Cooling technology	2-compressor cascade system			2-compressor cascade system
	Temperature setting range (°C)	-125~-150			-125~-150
	Climate type	N			N
	Capacity (L)	118			258
	2" box storage Qty (Pcs)	54			165
	Net weight (KGs)	165			280
	Internal W×D×H (mm)	540×400×560			780×500×660
	External W×D×H (mm)	1275×795×990			1510×885×1095
	Door entrance limit (≥mm)	780			885
	Cooling type	Direct			Direct
	Defrost	Manual			Manual
	Number of compressor	2			2
	Number of compressor	2			2
Control & display system	Controller	Microprocessor			Microprocessor
	Display	LED			LED
	Temperature display accuracy	0.1			0.1
Power	Power supply (V/Hz)	220/50	220/60	120/60	220/50
	Rated power (W)	1800	1800	1800	2450
	Rated current (A)	10.0	10.0	19.8	15.0
Alarm functions	Visible/audible alarm	●			●
	High/Low temperature	●			●
	Power failure	●			●
	Sensor failure	●			●
Monitoring	Cloud monitoring (Wi-Fi)	○ CryoMonitor 2000TF			○ CryoMonitor 2000TF
Accessories	Inner door	1			2
	Castors	6			6
	Test access port	Φ20mm x 1			Φ20mm x 1
	Safety door lock	●			●
	Freezer rack	○			○
	Rack model	CFC-9-2, 1×9			CFC-11-2, 1×11
	Rack Qty	6			15
	LN2 backup system	○			○
Material	Exterior	Pre-coated steel			Pre-coated steel
	Interior	Stainless steel			Stainless steel
	Insulation	Polyurethane			Polyurethane
	Cabinet insulation thickness (mm)	150mm			150mm
	Outer door thickness (mm)	105mm			105mm
	Compressor brand	SECOP			SECOP
Shipping	Gross weight (KGs)	208			292
	Packing W×D×H (mm)	1340×860×1140			1570×960×1230
	Volume (m³)	1.31			1.85