



CellVita Series CO₂ Incubator


Proven conditions, optimal cell cultures

Introduction

The Antech Scientific CellVita Series CO₂ incubators are engineered to meet the stringent demands of high-value cell culture. By maintaining a highly stable physiological environment, minimizing contamination risks, and offering a seamless user experience, the CellVita Series guarantees maximum viability and high reproducibility for sensitive biological samples.

Touchscreen Controller: Intelligent & Intuitive

The CellVita Series features a high-resolution, user-centric touchscreen controller that delivers exceptional visual clarity and intuitive menu navigation. The capacitive touchscreen is optimized for rapid response even when operated with laboratory gloves.




Event & data

NO.	Date	Time	Alarm description	End time
0	2026-06-11	09:02:42	T_M upper deviation alarm	2026-06-11 09:15:36
1	2026-03-10	11:28:51	T_M lower deviation alarm	2026-03-10 11:29:22
2	2026-03-09	16:30:09	CO ₂ miss upper limit	
3	2026-03-03	14:01:44	CO ₂ miss lower limit	2026-03-03 14:02:04

At the bottom of the screen, there are fields for 'Query' and buttons for 'Export' and 'Delete'.

Event and data are continuously logged and downloadable via USB, ensuring full traceability and compliance for seamless quality control and audit readiness.


Built-in Graphic




Achieve total peace of mind with continuous, on-screen curves that illustrates chamber conditions in real time.

Temperature Control: Uniformity You Can Trust

In cell culture, consistency is everything. Powered by a PID-controlled six-sided direct heating system, CellVita Series delivers an outstanding temperature uniformity of $\pm 0.3^{\circ}\text{C}$ across the entire chamber.



Temp Uniformity, $\pm 0.3^{\circ}\text{C}$



Temp Variation, $\pm 0.1^{\circ}\text{C}$

- Zero Cold Spots: Continuous, even distribution of warmth from all six sides.
- Rapid Recovery: Advanced direct heating technology ensures swift recovery after door openings.
- Optimal Cell Health: Minimizes environmental fluctuations to secure batch-to-batch reproducibility.

Upgrade to CellVita—where uniform warmth meets uncompromised cell health. Empower your next breakthrough with precision.

CO₂ Control: Accuracy Meets Convenience

Unmatched Precision

Engineered for sensitive cell cultures, the CellVita Series utilizes a state-of-the-art Infrared (IR) CO₂ sensor that delivers ultra-precise concentration management with a control precision of $\pm 0.1\%$.



Sensor Key Features

- NDIR dual beam technology
- Temperature and pressure compensated
- Heat-sterilizable up to 190°C
- Long lifetime
- Humidity correction

Effortless Convenience

- 180°C High-Heat Resistance: The robust IR sensor remains in situ during the sterilization cycle—no manual removal required, eliminating handling errors & potential contaminations.
- Recalibration-free: Integrated temperature and humidity compensation ensures the sensor retains factory-grade precision. No recalibration is needed after sterilization.

Advantages Over TC Sensors

Unlike traditional thermal conductivity (TC) sensors, this sophisticated optical IR sensor remains entirely unaffected by temperature and humidity fluctuations inside the chamber. This guarantees significantly shorter recovery times after door openings and maintains a uniform stability for sensitive cultures.


By keeping CO₂ boundaries strictly controlled, it actively prevents stressful pH shifts in culture media, protecting overall cell viability.

Oxygen Control (tri-gas, optional)

The CellVita Series offers an optional, precise oxygen control kit (controllable 1~21% O₂) to create physiological hypoxia, simulating in vivo microenvironments, which is essential for stem cells, primary cells, tumor cells, immune cells and organoids.

Advanced zirconia (ZrO₂) oxygen sensor withstands 180°C sterilization, eliminating the need for removal and reinstallation, which saves time and avoids any risk of recontamination.

Pro Tip: A multi-inner-door kit is recommended for reduced gas consumption and faster recovery after door openings.




Fast Recovery: Precision without Delay


In high-demand laboratories, frequent door openings are inevitable but present a severe threat to cell viability. The CellVita Series features a highly responsive control system paired with a forced-air convection loop to shorten recovery times down to mere minutes.

Ultra-Fast Parameter Recovery

Following a standard 30-second door opening, chamber temperature and CO₂ concentration recover within 5 minutes.



Temperature recovery curve



CO₂ concentration recovery curve

Eliminating Cellular Stress

This rapid CO₂ concentration recovery eliminates the risk of pH fluctuations in the culture media, safeguarding sensitive cells, such as stem cells and primary cultures, from metabolic shock and phenotypic drift.


Condensation-Free Stability

Accelerated thermal recovery prevents cold-spot formation on interior surfaces, eliminating condensation and cutting off the primary breeding ground for fungal contamination.

Maximizing Experimental Reproducibility

By shorten recovery time to mere minutes, CellVita guarantees that your cells spend most of its incubation period in a stable environment, delivering data consistency and GMP audit compliance.

Forced-air Convection with ULPA Filtration



The built-in blower and ULPA filter (ULPA filter not available for CellVita 55) generate a gentle forced air convection in chamber, bringing various benefits for cell culture:

- Uniformity: high uniformity of temperature, CO₂ concentration and humidity in chamber
- Cleanliness: ISO Class 5 cleanliness in chamber (for CellVita 185 & CellVita 260)
- Recovery: faster environment recovery after door openings:
 - Temperature & CO₂ concentration resumes within 5 minutes after a 30-second door opening
 - ISO Class 5 cleanliness resumes within 4 or 5 minutes after a 30-second door opening (for CellVita 185 & CellVita 260)

Ergonomic design


Mirror-Polished Stainless Steel Interior

The seamless, mirror-polished chamber eliminates cracks and crevices where contaminants can hide. This ultra-smooth surface significantly reduces bacterial attachment, ensures effortless cleaning, and provides maximum protection for your high-value cell cultures.




Perforated Shelves with Anti-slip design

Featuring an anti-slip safety design, these pull-out shelves eliminate the risk of accidental drops during retrieval. Shelf height adjustable, offering maximum flexibility for various applications.




Tempered Glass Inner Door with Access Port


The inner door allows sample observation without disturbing the incubation climate, while the access port enables seamless external probe connections, maximizing stability and contamination control.





Multi gas tight inner doors




CellVita 55 (2)



CellVita 185 (3/6)



CellVita 260 (4/8)



CellVita series provide multi gas tight inner doors option to bring various benefits:

Fast Recovery: Opening a small segmented door minimizes heat and CO₂ loss, enabling the chamber to return to setpoints much faster.



Gas Savings: Less gas escapes, significantly reducing CO₂/N₂ consumption and operational costs.

Humidity Retention: It prevents the loss of high humidity, safeguarding sensitive cells (like stem cells) from drying out.

Contamination Control: Smaller openings limit air turbulence, reducing the risk of airborne contaminants entering the incubator.

180°C Dry Heat Sterilization: 6-log SAL

In high-value cell culture, stem cell therapy, and translational medicine, contamination is the ultimate threat to experimental integrity. The CellVita Series CO₂ incubator integrates a fully in-situ, automated, overnight 180°C Dry Heat Sterilization cycle, establishing an uncompromising barrier against microbial risks. Sterilization reminder can be set on touch screen.



100% In-situ Sterilization

No need to remove the IR CO₂ sensor, ULPA filter, or optional O₂ and humidity sensors before sterilization. In-situ sterilization eliminates the risk of recontamination during reinstallation, providing maximum protection for sensitive cell cultures.

Regulatory Compliance

The 180°C sterilization process provides a push-button, highly reproducible, and fully automated cycle that drastically simplifies standard operating procedures (SOPs). By aligning seamlessly with the rigorous dry-heat sterilization standards defined by the USP (United States Pharmacopeia) and EP (European Pharmacopoeia), this technical approach guarantees compliance and audit readiness for clinical and industrial GMP laboratories.

Total Chamber Coverage

The meticulously engineered thermal airflow ensures uniform heat penetration into every square millimeter of the interior—including the fan assembly, shelving tracks, and structural blind spots.

Zero-Residue Safety

Unlike chemical fumigation techniques (e.g., vaporized hydrogen peroxide), dry heat is a purely physical process. It guarantees zero toxic chemical outgassing or residues, eliminating any risk of cellular stress or chemical interference with your precious cultures, while ensuring maximum safety for laboratory personnel.

Definitive Microbial Eradication (6-log SAL)

Operating at a sustained 180°C, the cycle utilizes thermal oxidation to irreversibly denature microbial proteins and liquefy lipids. It achieves a proven Sterilization Assurance Level (SAL) of 6-log, completely eliminating the most resilient biological threats, including *Geobacillus stearothermophilus* endospores, stubborn fungi, vegetative bacteria, and mycoplasma.

Microorganisms eliminated during the high-temperature sterilization cycle

Microorganism	ATCC	Average colony count of control group (CFU/piece)	Log reduction value (KL)	Kill rate (%)
<i>Escherichia coli</i>	8099	1.0×10^7	> 6	> 99.9999
<i>Staphylococcus aureus</i>	6538	9.0×10^6	> 6	> 99.9999
<i>Pseudomonas aeruginosa</i>	15442	7.8×10^6	> 6	> 99.9999
<i>Staphylococcus albus</i>	8032	8.8×10^6	> 6	> 99.9999
<i>Bacillus atrophaeus</i> spores	9372	1.1×10^7	> 6	> 99.9999
<i>Geobacillus stearothermophilus</i>	7953	1.2×10^7	> 6	> 99.9999
<i>Aspergillus brasiliensis</i>	16404	2.2×10^7	> 6	> 99.9999

Note: Mean value of three independent experiments performed on different dates; sterilization temperature: 180°C, exposure time: 45 min


MicroStat™ Antimicrobial Powder Coating

The CellVita Series features the MicroStat™ antimicrobial powder coating on exterior surfaces. It actively inhibits the adhesion and growth of common contaminants such as *S. aureus* and *E. coli*, reducing cross-contamination risks. By resisting microbial-induced discoloration and corrosion, MicroStat™ keeps your incubator looking new for years and simplifies routine cleaning.

Duration of action	Test Item	Test Strains	Colony count of negative control after 24h (CFU/carrier)	Colony count of blank sample after 24h (CFU/carrier)	Colony count of test sample after 24h (CFU/carrier)	Antibacterial rate (%)
24 h	Antibacterial Performance	<i>Escherichia coli</i>	2.8×10^9	3.1×10^9	1.7×10^7	99.45
		<i>Staphylococcus aureus</i>	6.2×10^8	9.1×10^8	3.5×10^5	99.96
	Durability of Antibacterial Property	<i>Escherichia coli</i>	4.6×10^9	5.4×10^9	<1000	>99.99
		<i>Staphylococcus aureus</i>	5.5×10^8	6.5×10^8	<1000	>99.99

Cloud-based Monitoring, Optional

CellVita Series offers cloud-based 24/7 remote monitoring via its built-in Wi-Fi module. This ensures real-time performance tracking and instant mobile alerts for critical deviations, maximizing culture security, data integrity, and ultimate peace of mind.



Ordering information

Standard equipment	Description	Cat. No. CellVita 55	Cat. No. CellVita 185	Cat. No. CellVita 260
CellVita CO₂ incubator				
CellVita CO ₂ incubator	220V, 50/60Hz	6111110	6111210	6111310
CellVita CO ₂ incubator	120V, 60Hz	6111140	6111240	6111340
Options (factory installed: order with standard equipment)				
Door hinged	Left	6100180	6100280	6100380
O ₂ control, ZrO ₂ sensor, 180°C in-situ sterilization	O ₂ control, Vol-% 1 to 21 incl. 2 gas tight inner doors	6100110	-	-
	O ₂ control, Vol-% 1 to 21 incl. 3 gas tight inner doors	-	6100210	-
	O ₂ control, Vol-% 1 to 21 incl. 6 gas tight inner doors	-	6100220	-
	O ₂ control, Vol-% 1 to 21 incl. 4 gas tight inner doors	-	-	6100310
	O ₂ control, Vol-% 1 to 21 incl. 8 gas tight inner doors	-	-	6100320
2 gas tight inner doors		6100120	-	-
3 gas tight inner doors		-	6100230	-
6 gas tight inner doors		-	6100240	-
4 gas tight inner doors		-	-	6100330
8 gas tight inner doors		-	-	6100340
Humidity sensor for accurate display, 180°C in-situ sterilization		6100030	6100030	6100030
Water level monitor		6100040	6100040	6100040
Wi-Fi connection, with 10-year cloud platform service		6100050	6100050	6100050
Accessories				
Additional standard shelf, max. load 15 kgs		6100150	6100250	6100350
Heavy duty shelf, max. load 20 kgs		6100160	6100260	6100360
Shelf, solid copper		6100151	6100251	6100251
Shacker, used in CO ₂ incubator, CO ₂ resistant, try size 365x350mm		-	6100060	6100060
Roller base		6100170	6100270	6100370
Gas cylinder switch		6100010	6100010	6100010
Gas regulator for CO ₂ /N ₂		6100020	6100020	6100020

Technical specifications

Model			CellVita 55	CellVita 185	CellVita 260
Basic	Chamber volume	liter	55	185	260
	Controller		7" touch screen		
	Construction		Direct heating		
	CO ₂ sensor		Infrared (IR) sensor		
	Sterilization		180°C dry heat, 6-log SAL		
Temperature	Control		6-sided direct heat, PID controlled		
	Range	°C	Ambient +3 to 60		
	Accuracy	°C	±0.1		
	Uniformity	°C	±0.3		
	Fluctuation	°C	±0.1		
	Ambient range	°C	18~34		
	Temperature recovery time	minutes	≤5	≤5	≤5
CO ₂	Control		PID controlled		
	Range	Vol - %	0~20		
	Accuracy	Vol - %	±0.1		
	CO ₂ sensor		Infrared (IR) sensor		
	CO ₂ recovery time	minutes	≤5	≤5	≤5
	Inlet pressure	bar	0.8~1.2		
	Gas purity		Min. 99.5%; industrial quality min.		
	CO ₂ inlet		ID 6mm hose with 0.2µm inlet filter		
O ₂ , optional	Range	Vol - %	1~21		
	Accuracy	Vol - %	±0.1		
	O ₂ sensor		Zirconium oxide		
	Multi gas-tight inner doors		2	3 or 6	4 or 8
	Inlet pressure, N ₂	bar / PSI	0.8 ~ 1.2 / 12~17		
	Gas purity		Min. 99.5%; industrial quality min.		
	N ₂ inlet		ID 6mm hose with 0.2µm inlet filter		
Humidity	Range	% RH	High humidity mode: ≥90; Low humidity mode: 80~90		
	Humidity reservoir		Water pan, Max. 3 L		
	Humidity display		○		
	Water level monitor		○		
	Cycle temperature	°C	180		
Sterilization	Cycle duration		< 10 h		
	Sterilization reminder		●		
Control	Controller		7" touch screen		
	Data & event		Data & event memory, download via USB port		
	Data & signal outputs		USB, RS485, remote alarm contact		
	Built-in graphic		Temperature, CO ₂ concentration		
	Alarm as standard		Temperature, CO ₂ concentration, door open, sensor failure		
	Alarm as optional		O ₂ concentration, RH, low water level		
	Wi-Fi connection for remote monitoring		○		
Construction	Type		6-sided heating		
	Interior chamber		SUS 304, mirror-finished		
	Exterior casing		Electrogalvanized steel with MicroStat™ antimicrobial powder coating		
	Access port		Ø32mm x 1, at back		
	Sampling hole		Ø6mm x 1, on inner door		
	Inner chamber blower		●		
	ULPA filter		-	●	●
	Stackable kit		●		
Dimensions	Internal dimensions (w x d x h)	mm	310×380×470	500×570×650	555×570×832
	External dimensions (w x d x h)	mm	530×635×690	715×820×870	775×820×1055
	Net weight	Kg	60	85	110
Shelves	Dimensions (w x d)	mm	306×270	490×461	549×461
	Number std./max.	pcs	2/12	3/12	3/12
	Max. load per shelf	Kg	15		
	Construction		Perforated SUS 304, anti-slip design, distance adjustable		
Electrical	Power supply		220V, 50/60Hz; 120V, 60Hz		
	Nominal power at 37°C	W	65	85	110
	Maximum power	W	600	1300	1600
	Full load amps, 220V, 50/60Hz	A	3	6	7
	Full load amps, 120V, 60Hz	A	6	12	14
Shipping	Packing size(w x d x h)	mm	590×700×860	770×900×1050	835×870×1230
	Gross weight	Kg	75	110	120



Qingdao Antech Scientific Co., Ltd.

Tel: +86 532 87890321

Email: info@antechscientific.com

Web: www.antchscientific.com

